

MK-110, MK-110-A Embedded Chassis for Mini-ITX Motherboard with One/Two Expansion Slots



Features

- Front I/O interface
- Shock-resistant bay space for one slim-type optical drive and 3.5" disk drive
- Cutouts for three COM, two DVI/LVDS, one S/C-video
- Supports both AC(180W) and DC(200W) ATX PFC power supply options
- Reusable and washable air filter
- MK-110 supports one expansion slot, MK-110-A supports two expansion slots

Specifications

Dimensions	9.8 in x 6.1 in x 10 in (250 mm x 156 mm x 241 mm) (W x H x D)
Drive Bays	One 3.5" HDD internal drive bays One slim-type CD/DVD-ROM
Construction	Heavy-duty steel
Color	Standard: gray
Cooling Fans	One 92 mm x 92 mm x 25 mm ball bearing fan
Front Panel	LEDs: HDD activity and system power System reset switch and ATX power switch
Power Supply	Supports Flex ATX power supply
Carton Size	15.5 in x 14.6 in x 10.8 in (395 mm x 375 mm x 275 mm)
Weight	Net 3 kg (6.6 lb)

Power Supply Options

Model Number	Watt	Input Range	Output (Max.)					
			+5V	+3.3V	+12V	-12V	-5V	+5Vsb
APS-925XU	250 W	Universal	14 A	12 A	18 A	0.3 A	-	2.5 A

Ordering Information

Model Number	Color	Power Supply
MK-110	Gray	-
NS-110MI-250	Gray	APS-925XU
MK-110-A	Gray	-
NS-110AMI-250	Gray	APS-925XU

Mechanical Layout



MK-110

MK-110-A



Dimensions

Units: mm

