

GH-241ATX/242ATXR

2U Rackmount Chassis

19" Rackmount



Specifications

- **EIA RS-310C 19" Rackmount Standard**
- **Construction:** Heavy Duty Cold Rolled Electroplated Steel
- **Color:** Beige or Black or Custom Design
- **System Boards:** Dual Xeon, Pentium 4, Dual Pentium III
- **Support ATX M/B(Max. to 12"x13")**
- **Backplane:** "SCAM" Compliant Support SE, LVD, U2 & Ultra 160 System Transfer Rate up to 160MB/Sec
- **Drive Capacity:** 1x5.25" & 1x3.5" & 4x3.5" Hot Swappable SCSI-160 Trays
- **Power Supply(Optional):** 2U Single 250~400W ATX P/S(GH-241ATX)
2U Redundant 300~350W ATX P/S(GH-242ATXR)
(Rear Installation)
- **Cooling:** 4x(8cm) Fans(42.5CFM ea.)
- **Expansion Slots:** 2 or 3xHorizontal ISA/PCI/AGP Type Slots
- **Indicators:** Leds for Power ON/OFF, HDD Active
- **Switch:** Power ON/OFF, System Reset
- **Thermal Management Card Installed**
- **Dimensions:** 483(W)x88(H)x650(D)mm(19"x3.5"x25.6")
- **Cuft:** 4.4
- **GW:** 17kgs / 37.5lbs
- **Carton Size(cm):** 58.8x25.5x82.5(23.1"x10.0"x32.5")
- **Product Applications:** Web Server, Email Server, RAID Server, Proxy Server, High-End Workstation, Print Server, File Server

Dimension

